

Technical Data Sheet

SO SNOW CAP

PVC CAPPING SEAL



Description

SO SNOW CAP is a flexible pvc capping seal used to finish the top of a resilient floorcovering where it has been covered up the wall. Capping seals are usually used in conjunction with a cove former.

Installation

SO SNOW CAP should be allowed to acclimatise for 24 hours prior to installation at an ambient temperature of 18° Celsius.

1. It should be ensured that all surfaces to which the profile is to be fixed are sound, dry, flat and free from any contaminants. Wall surfaces should be free from any previous coverings, linings or adhesive residues used to fix them. Paint films and any mould must be removed and the affected surface treated correctly.
2. Mark the position of the top of the capping seal on the wall and strike a straight line between the two points using a chalk line.
3. Apply a suitable contact adhesive and follow the manufacturers instructions for application.
4. Bring both surfaces together and apply even pressure along the capping seal ensuring any air bubbles are removed and full contact is made with the wall.
5. All internal corners should be mitre cut. External corners may be mitre cut or wrapped around the corner providing adequate provision is taken to allow the floorcovering to be installed. It can then be fitted into the top channel of the capping seal.

Cleaning and maintenance guidelines:

These guidelines have been compiled to help the user obtain optimum performance and satisfaction.

Preventative Maintenance Programme

- A regular scheduled maintenance programme should be employed to prevent the build up of dirt and grease, which will detract from the overall appearance of the product.

Daily Cleaning

- Brush down the profile using a soft bristled brush and remove dust particles by wiping with a damp cloth.

Twice Weekly or as Required

- Brush down the profile using a soft bristled brush. With clean warm water, apply a small amount of a soap-less detergent to a lint free cloth and gently clean the surface. During the clean, the water must be changed on a regular basis. Once the profile has been cleaned thoroughly rinse with fresh, clean water and dry with a dry lint free cloth.
 On completion the profile should be completely dry.

NB. The use of an aggressive detergent could result in colour fade within the PVC.

Floor sealants, polishes or such coating should not under any circumstances be applied to PVC.

Technical Data	
Type:	Capping Seal
Environment:	Interior
Used with:	Resilient Floorcovering
Material:	Flexible PVC
Height:	40mm
Gauge:	2mm
Length:	2.0m
Colour:	Snowdrift (LRV 80.86)
Fixing:	Adhesive Fix

