

# CS150

## ACRYLIC PRIMER



### KEY BENEFITS SUMMARY

- Easy to apply
- Helps to prevent pin-holing
- Helps maintain the flow characteristics of the screed

### PRODUCT INFORMATION

#### Description

CS150 Acrylic Primer is a universal primer for porous substrates.

#### Usage/Purpose

CS150 Acrylic Primer is specifically designed for use as a primer for polymer screed applications or beneath smoothing compounds on porous substrates.

#### Colour

White

#### Packaging

CS150 is supplied in 25 litres and 5 litres.

#### Standards

All aspects of the installation must be in accordance with the requirements of BS 8204, BS 8203 (Installation of Resilient floorcoverings) or BS 5325 (Installation of Textile floorcoverings) and supplementary specifications.

#### Protective Equipment

Use in well ventilated conditions and ensure all recommended protective equipment is worn during handling & use of this product. For full recommendation, refer to safety data sheet.

#### Preparation

- Ensure all surfaces to be coated are clean, dry, frost free and free from grease, oil, dirt, dust, loose friable material and any other contaminants.
- Mechanical preparation, using an enclosed shotblasting machine, may be recommended and should be followed by thorough vacuuming to remove all surface dust.

#### Application

- Apply by brush or roller ensuring a continuous film, avoiding puddles and ensuring all the surface is coated.

#### Health & Safety Precautions

Safety data sheet must be read and understood before use.

#### Availability

Direct from tremco illbruck (see back of leaflet for address and telephone details), or via local and national distributors.

#### Technical Service

tremco illbruck has a team of experienced Technical Sales Representatives who provide assistance in the selection and specification of products. For more detailed information, service and advice, please call Customer Services on 01942 251400.

#### Guarantee/Warranty

tremco illbruck products are manufactured to rigid standards of quality. Any product which has been applied (a) in accordance with tremco illbruck written instructions and (b) in any application recommended by tremco illbruck, but which is proved to be defective, will be replaced free of charge.

No liability can be accepted for the information provided in this leaflet although it is published in good faith and believed to be correct.

tremco illbruck Limited reserves the right to alter product specifications without prior notice, in line with Company policy of continuous development and improvement.

# CS150

ACRYLIC PRIMER

TREMCO

## TECHNICAL DATA

PROPERTY	RESULT
Composition	An aqueous based co-polymer dispersion
Density	1.02 g/ml
pH	7-9
Solubility in Water	Miscible
Freezing Point	0°C
Coverage	8 m <sup>2</sup> per litre depending on substrate
Storage	Store in dry conditions between +5°C and +35°C
Shelf Life	6 months when stored as recommended in original unopened containers



2019-12