

LVT gluedown

## Specification



plank



herringbone

Planks per Pack	12	32
Pack Coverage	2.73m <sup>2</sup>	2.23m <sup>2</sup>
Packs per Pallet	100	112
Pallet Coverage	273m <sup>2</sup>	249.76m <sup>2</sup>
Plank Dimensions	1229 x 185 mm	590 x 118 mm
Wear Layer	0.55 mm	0.55 mm
Thickness	2.5 mm	2.5 mm
Total Weight	12.5 kg	11.24 kg

## Test Results

Castor Chair Wheel (EN 425)	Pass
Abrasion Resistance (EN 660-2)	T Grade
Indentation Residue (EN 433)	Pass
Colour Fastness (EN ISO 105-B02)	≥6
Fire Rating (EN13501-1)	B <sub>FL-s</sub> 1
Effects of Stain (EN 423)	Pass
Residual Indentation after Stability (EN 434)	Shrinkage ≤ 0.08% Curling ≤ 2.0 mm
Flexibility - 10mm Mandrel (EN 435)	No Damage
Resistance to Chemicals (EN 423)	Class 0
Peeling Strength of Layers (EN 431)	Pass
Toxic (EN 71Part3)	Pass
Slip Resistance (DIN 13893)	R10, 36+
Performance Classification (EN 685)	23/34/43
GB/T 4085 GB86t24 B1	Pass
CNS 8907	Pass