

Texstar

Datasheet

Classification	Norm	Tarkett Value
Product type	EN ISO 26986	Expanded (cushioned) poly(vinyl chloride) floor covering
Domestic classification	EN ISO 10874	23 Heavy
Commercial classification	EN ISO 10874	32 General
Binder content	ISO 11638	Type I
Characteristics	Norm	Tarkett Value
Total thickness	ISO 24346	2.80 mm
Wear layer thickness	ISO 24340	0.35 mm
Total weight	ISO 23997	1760 g/m²
Performance for CE Marking	Norm	Tarkett Value
Declaration of Performance	EN 14041	0007-0016-DOP-2022-03
Reaction to fire	EN 13501-1	Cfl-s1
Slip resistance (EN 13893)	EN 13893	Class DS ($\mu \geq 0.30$)
Slip resistance (DIN 51130)	DIN 51130	R10
Electrical Propensity	EN 1815	Antistatic (≤ 2 kV)
Thermal resistance (m² K/W)	ISO 10456	0,030 m²•K/W
Technical Performance	Norm	Tarkett Value
Residual indentation	EN ISO 24343-1	≤ 0.20 mm
Castor chair effect	ISO 4918	No damage after 25000 cycles
Impact sound reduction - ΔL_w	EN ISO 717-2	19 dB
Colour fastness to light	ISO 105-B02	≥ 6
Chemical resistance	ISO 26987	Not affected
Underfloor heating		Suitable (subfloor temperature maximum 27°C)
Dimensional stability	EN ISO 23999	$\leq 0,15$ %
Curl resistance to heat	ISO 23999	≤ 8 mm
Sustainability, Environment & Indoor Air Quality	Norm	Tarkett Value
Recyclable		Yes - offcuts and post-use through ReStart® (ISO 14021)
Recycled Content (up to)		32 %
Carbon Footprint (Cradle-to-Gate, EPD Modules A1-A3)		5.50 kg CO ₂ e /m²
Phthalate free		Yes
TVOC emissions after 28 days	EN 16516	Gold
BREEAM rating		A+
Formaldehyde emission		E1
EPD		Yes
Material Health Statement		Yes
SCS Floorscore		Yes
French emissions label		A+
Allergy UK Seal Of Approval		Approved
Dimensions and designs		
Roll		Roll 2x25m Roll 3 x 25 m Roll 4 x 25 m
Number of designs available		16



The above information is subject to modification for the benefit of further improvement (23/01/2026). According to the European Regulation N°305/2011 for CE Marking, the Declarations of Performance are available on our website <https://www.tarkett.com> Tarkett's instructions regarding installation, cleaning and maintenance should be observed. Please contact Tarkett at the address shown for the instructions.